



BARRICADE®
BEAR CAULK™



POLYETHER DOOR & WINDOW CAULK

Barricade® Bear Caulk™ is a single-component, solvent-free Silyl Modified Polyether hybrid caulk formulated to work in conjunction with Barricade Flash Right™ flashing tape. When you need a flexible and waterproof (when cured) caulk to seal window and door framework as well as expansion and control joints, Bear Caulk is the right choice.

Professionals know it is the finishing touches that differentiate a job from a job well done. With Barricade Bear Caulk, all of your jobs will finish with the high-quality performance you expect from Barricade.

KEY FEATURES

- Meets ASTM C920, Class 50
- Permanently flexible
- Quick paint-over time
- No water washout
- Non-yellowing, color-fast aesthetics
- Asphalt compatibility
- Guaranteed compatibility with Barricade® Flash Right™ & Barricade® Flash Ulti™ flashing

RECOMMENDED FOR

- Vinyl & aluminum windows
- Wood windows & doors
- Flashing papers & membranes
- Trim & molding
- Concrete, brick, & cement

KEY STANDARDS

- ASTM C920, Type S, Grade NS, Class 50, Use NT, A, O
- CARB and SCAQMD Compliant
- Meets VOC Requirements for OTC Regulation
- AAMA Compliant 713-10, 808.3-10
- US Federal Specification TT-S-00230C, CAN/CGSB 19.13-M87

SPECIFICATIONS

Composition	Tubes/Case	Shelf Life	Nail Sealability	TYPICAL UNCURED PROPERTIES		TYPICAL CURED PROPERTIES AFTER 14 DAY CURE AT 77°F AND 50% RELATIVE HUMIDITY		Warranty
				Extrusion Rate	Flash Point	Hardness Shore A ASTM D2240	Tensile Strength ASTM D412	
One-component, solvent-free Silyl Modified Polyether (hybrid) sealant	24	12 months	Pass	70°F, 50psi (ASTM C603) Modified - 140 g/min	135°F 57.2°C	38	180 psi	1-Year Limited when used with Barricade® Flash Right™

Note: The information contained in this data sheet is, to the best of our knowledge, true and accurate and is presented in good faith. Barricade Building Products assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents. Contact Barricade Building Products for further information or technical support.



BARRICADE®
BUILDING PRODUCTS

Find more information at:
barricadebp.com/bear-caulk
1-877-832-0333