



## WHY CHOOSE BARRICADE® UDL

Barricade® UDL Standard roof underlayment is suitable for all roof coverings and offers a 20-year limited warranty, backed by high-performance features that benefit both builders and homeowners.

### BENEFITS

#### Non-skid coating

Barricade UDL Standard has a non-skid coating for safe installation.

#### More coverage

14% more coverage per lap (48-inch width compared to 42-inch synthetics)  
33% more coverage per lap (48-inch width compared to 36-inch felt)

#### Ease of installation

Lies flat and doesn't wrinkle.

#### Faster Installation

48-inch width means faster installation and savings on labor costs.

#### UV resistance

Barricade's special ultraviolet stabilizers protect it from the sun's harsh rays for up to 60 days.

#### Water resistance

Protection against water elements, ensuring a strong, protective, and reliable installation.

#### Code Compliant

- ASTM D226 I & II, ASTM D4869 II & IV
- Florida #17858-R1



#### Coverage

Approximately 916 sq. ft. per roll or less, depending upon overlap and roof design



#### Superior wind and tear resistance

Heavy winds pose a threat to roof underlayment during installation. With its tear-resistant design, Barricade UDL Standard is a superior durable underlayment.



#### Cool gray surface

Barricade UDL Standard's cool gray surface is up to 30° cooler than black underlayment.



#### UV resistance

Barricade UDL Standard is protected against UV rays for up to 60 days.



## BARRICADE® UDL STANDARD OUTPERFORMS THE COMPETITION

Barricade UDL Standard is suitable for all roof coverings. Available in 5 or 10 square rolls, Barricade UDL Standard provides superior tear resistance and superior strength compared to felt.

### Preparation

The deck surface must be dry and free of dust, dirt, loose nails, debris, and other protrusions. Damaged sheathing must be replaced. Ensure that the space beneath the roof sheathing is properly ventilated before installing to avoid condensation problems.

### Installation

Barricade UDL Standard is laid out horizontally (parallel) to the eave, with the printed side up, using 4" horizontal laps and 6" vertical laps. Follow codes for low slopes as defined as 2:12 to 4:12 and steep slopes greater than 4:12 applications. Barricade UDL Standard is designed to withstand 60 days of exposure prior to being covered with the final roofing material. Barricade® recommends covering Barricade UDL Standard with the final roofing material as soon as possible.

### Fasteners

Barricade® recommends attaching Barricade UDL Standard to structural roof deck material using plastic cap, ring shanked roofing nails that have a minimum 1" diameter cap. Anchoring to be installed at a minimum per surface markings, spaced 6" on-center in vertical and horizontal laps, and 12" on-center along the center of the roll. If the application of Barricade UDL Standard and the final roofing material occur on the same day, then the option to use every other printed anchoring placement is acceptable. For same day coverage, corrosion resistant 3/8" head and 1" leg roofing nails are acceptable as well as 1" plastic cap staples. High slope roofs, (> 7/12 pitch) must use plastic cap nails. All anchoring devices must be flush, 90° to the roof deck, and tight with the underlayment surface and the structural roof deck.

### CAUTION - READ GOOD SAFETY PRACTICES BELOW

As with any roofing product, always follow safe roofing codes and practices (OSHA), and always use fall-protection devices when working on roofs (i.e. toe boards, rope harnesses, and rubber or synthetic soft-sole footwear). Use caution when walking or standing on Barricade UDL Standard as wet and/or dusty conditions may reduce traction. Failure to use proper safety gear and footwear can result in serious injury.

## SPECIFICATIONS

Meets Standards	Standard Sizes	Total Weight	Water Transmission ASTM D4869	Water Vapor Transmission ASTM E96	UV Exposure Rating	Warranty
ASTM D226 I & II ASTM 4869 II & IV FL #17858-R1	48" x 125' 48" x 250'	9 lbs/roll 19 lbs/roll	Pass	1 US Perm	60 Days	20-Year Limited Warranty

\*The information contained in this data sheet is, to the best of our knowledge, true and accurate and is presented in good faith. Barricade Building Products assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents. Contact Barricade Building Products for further information or technical support.



**Find more information at:**  
[barricadebp.com/udl-standard](http://barricadebp.com/udl-standard)  
 1-877-832-0333