BARRICADE® SEAM TAPE™

CONSTRUCTION SEAM TAPE

Optimize your home's weather resistance capability by implementing Barricade® Seam Tape as part of the wall envelope's secondary line of defense against exterior moisture penetration. Provide added protection against energy robbing air infiltration and maximize energy efficiency by sealing the gaps, cracks, and crevices where air can easily penetrate the home, and ultimately affect your heating and cooling costs.

RECOMMENDED FOR

- Door flanges/frames
- Repairing small (less that 5" diameter) rips, punctures, or tears in the sheathing or building wrap material
- building wrap seams & overlaps
- Exterior wall sheathing joints
- Patching job site damage caused by fragile wall sheathings such as foam and fiberboard
- Sealing building wrap seams installed over head flashings

For use on windows & doors, cornerboard abutments, sidewall sheathing seams, and deck-to-wall joints. For more information about Barricade's extensive line of flashing tapes, building wraps, and underlayment materials, contact your Barricade sales representative today!

SPECIFICATIONS

Composition	White polypropylene film coated with a cold-weather acrylic adhesive system	**Tensile Strength**	30 lbs/in
Sizes	1⅞" x 165', 3" x 165'	**Elongation**	140%
Rolls/Case	16	**Adhesion**	40 oz/in
VOC Content	=0.1%	**Moisture Vapor Transmission Rate**	3.9x10-9 g/Pa s m^2
Total Thickness	3 mils	**Water Retention Rate**	0.009 g/100 in^2
Application Temperature	14°F – 122°F (-10°C – 50°C)	**Shelf Life**	12 months
Temperature Resistance	-40°F – 212°F (-40°C – 100°C)	**UV Exposure Rating**	6 months
		Warranty	20-Year Limited System

Note: Barricade Building Products strongly recommends the additional use of an approved flashing material (one that meets or exceeds Fed. Spec. UU-B-790a Grade A and is a minimum of 6" in width) around windows and doors. Barricade Seam Tape by itself, should not be used as a flashing material and when it is not used in conjunction with an approved flashing material, may compromise the wall systems ability to effectively resist exterior moisture penetration. Barricade® Building Products assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents. Contact Barricade Building Products for further information or technical support.

BARRICADE® BUILDING PRODUCTS

Find more information at:
barricadebp.com/seam-tape
1-877-832-0333

© 2023 Barricade® Building Products