



POLYETHER DOOR & WINDOW SEALANT

Barricade® Construction Sealant™ is a single-component, solvent-free Silyl Modified Polyether hybrid sealant formulated to work in conjunction with Barricade Flash Right™ flashing tape. When you need a flexible and waterproof (when cured) sealant to seal window and door framework as well as expansion and control joints, Construction Sealant is the right choice.

Professionals know it is the finishing touches that differentiate a job from a job well done. With Barricade Construction Sealant, all of your jobs will finish with the high-quality performance you expect from Barricade.

KEY FEATURES

- Meets ASTM C920, Class 50
- Permanently flexible
- · Quick paint-over time
- No water washout
- · Non-yellowing, color-fast aesthetics
- · Asphalt compatibility
- Guaranteed compatibility with Barricade® Flash Right™ & Barricade® Flash Ulti™ flashing

RECOMMENDED FOR

- Vinyl & aluminum windows
- Wood windows & doors
- Flashing papers & membranes
- Trim & molding

TYPICAL CURED PROPERTIES
AFTER 14 DAY CURE AT 77° AND 50% RELATIVE HUMIDITY

· Concrete, brick, & cement

KEY STANDARDS

- ASTM C920, Type S, Grade NS, Class 50, Use NT, A, O
- · CARB and SCAQMD Compliant
- Meets VOC Requirements for OTC Regulation

TYPICAL UNCURED PROPERTIES

- AAMA Compliant 713-10, 808.3-10
- US Federal Specification TT-S-00230C, CAN/CGSB 19.13-M87
- Should be stored at >41°F prior to use

SPECIFICATIONS

Composition	Tubes/Case	Shelf Life	Nail Sealability	Extrusion Rate	Flash Point	Shore A ASTM D2240	Tensile Strength ASTM D412	Warranty
One-component, solvent-free Silyl Modified Polyether (hybrid) sealant	24	12 months	Pass	70°F, 50psi (ASTM C603) Modified – 140 g/min	135°F 57.2°C	38	180 psi	1-Year Limited when used with Barricade® Flash Right™



Note: The information contained in this data sheet is, to the best of our knowledge, true and accurate and is presented in good faith. Barricade Building Products assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents.

Contact Barricade Building Products for further information or technical support.

Find more information at: barricadebp.com/construction-seam-tape/barricade-construction-sealant 1-877-832-0333