



BARRICADE® LIQUID FLASH



LIQUID FLASH

Seal out leaks and protect your build with **Barricade® Liquid Flash**, a powerful, self-adhering flashing membrane designed to protect windows and doors from moisture penetration.

This easy-to-use, single-component Silyl-Terminated Polyether (STPE), guns, spreads, and tools smoothly to create a durable, seamless, and flexible waterproof flashing membrane. It's ideal for preparing sheathing joints before applying air or water-resistive barriers—and it cures fast, allowing for same-day installation of windows, doors, and other components.

Net Weight: 20 fl oz (590 ml)

SPECIFICATIONS

Composition	Packaging	Sausages Per Case	Permeability	Tensile Strength	Application Temp Range	Operating Temp Range	Application Thickness	Warranty	Shelf Life	UV Exposure Rating	AAMA 714	ASTM E84
One-component, solvent-free Silyl Modified Polyether (hybrid) sealant	20 fl oz Sausage	12	13.6 perms	>120psi	>40°F >4.4°C	-40°F - 200°F	12-15 mils	1-year Limited	18 Months	12 Months	PASS	Class A Fire Rated

The information presented herein was prepared at INDEVCO Building Products by qualified technical personnel. To INDEVCO's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data is submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which INDEVCO assumes any legal responsibility.

Adhesion:

Barricade Liquid Flash adheres well to a wide variety of substrates, generally with no primer required. It can bond to damp substrates and cure in wet weather.

Application:

The recommended application thickness is 12-15 wet mils. At this thickness, the estimated coverage is 1ft² per 0.8 fl. oz. Surfaces must be clean and free of contaminants. It is recommended to test substrate compatibility with Barricade Liquid Flash prior to full application. Curing/drying speed will be influenced by temperature and humidity conditions.

Recommended Uses:

- For use as a membrane for flashing rough openings, and as a detailing compound for preparing sheathing joints for application of an air/water-resistive barrier membrane.
- Acceptable substrates include ASTM C1177 sheathing, plywood, pressure treated wood, OSB, steel, aluminum, and CMU (concrete masonry units).

Features:

- Can be applied to damp substrates
- Withstands rainfall immediately after application
- Fast cure and tack-free time
- Easy application – no mixing required
- Bonds to a wide range of substrates
- May be fully exposed to UV and weather for up to 12 months
- Breathable – allowing damp surfaces to dry
- Does not contain solvents, PVC or isocyanates



Find more information at:
barricadebp.com
1-877-832-0333

